



PRODUCT DATA SHEET MODEL ICR18650J

Cylindrical / Steel Max. 18.40mm **■CELL SPECIFICATIONS** Shape / Can material 2370mAh Typical Capacity Minimum Capacity 2300mAh Nominal Voltage 3.76V Charge Voltage $4.2V \pm 0.05V$ Charge Current Less than 2.4A Charge Time 3.0 hrs $5.0 \text{ A } (\leq 45 \,^{\circ}\text{C})$ Max. Discharging current (Max.) 65.15mm $4.0 \text{ A} (\leq 60 \, ^{\circ}\text{C})$ Discharge Cutoff Voltage 2.5V 0°C to 45°C Charge Temperature Discharge -20°C to 60°C Storage -20°C to 60°C Weight (Max.) 48.0g Diameter 18.40mm Dimensions (Max) Height (Max.) 65.15mm Energy Volumetric 517 Wh/I Density Gravimetric 187 Wh/kg


Note: The **ICR18650J** cylindrical cell consists of a lithium cobalt oxide positive electrode and a graphitic carbon negative electrode providing 3.76volts and 2370mAh. This cell design requires pack control circuitry. Various protection circuit modules are available for applications of multiple series and parallel configurations. In order to ensure safe use of cell, be sure to consult with **E-One Moli Energy** regarding charging and discharging specifications and contact E-One Moli Energy in advance when designing a device with this cell.

PRODUCT DATA SHEET MODEL ICR18650J







■Discharge Rate Characteristics



■Discharge Temperature Characteristics



■Cycle Characteristics



Molicel ICR18650J Applications:

- * Notebook
- * HID handy flash
- * Medical devices

- * Portable VCD/DVD player
- * Camcorder

E-ONE MOLI ENERGY CORP was established in 1998 by Koo's Group. Under the brand name Molicel, E-One Moli Energy is well-recognized as a leading Li-ion battery manufacturer. To serve world-wide customers, production sites are located in Vancouver, Canada and Southern Taiwan Science Park, Tainan, Taiwan. Each site is equipped with local Research & Development and Application Service Groups. Safety and reliability are the main strengths of E-One Moli Energy products. We strive to provide superior energy solutions with high performance and quality products that serve our customers' needs.

■ Taiwan Plant
10 Dali 2nd Rd., Shan-Hwa,
Tainan County, Taiwan, R.O.C.
Tel: 886-6-505-0666
Fax: 886-6-505-0777
http://www.e-one.com.tw

■ Canada Plant 20,000 Stewart Crescent Maple Ridge, B.C., Canada, V2X 9E7 Tel: 1-604-466-6654 Fax: 1-604-466-6600 http://www.molienergy.com ■ Headquarter 10F, 113, Sec.2, Zhung Shan N Rd., Taipei, Taiwan, R.O.C. Tel: 886-2-2567-3500 Fax: 886-2-2567-6500

Agency:			